

BHE 75 Plus

BATHROOM RADIATOR

PRODUCT-NO.: 238713

Heat your bathroom the convenient way

These electric bathroom radiators supply you efficiently with the right amount of heat, just where you need it, all year round. Their blend of appealing design and functionality is a real winner. The operating controls are fitted at the perfect height for you to be able to adjust the temperature with ease.

Multiple uses of heat

Thanks to the slender round pipes and evenly distributed heat, you can hang your hand and bath towels on the radiator at several levels to dry or warm up. With their particular properties, the bathroom radiators in this series are ideal for use as heat generators or interim heaters in spring/autumn.

The main features

Electric-only operation due to factory filling with heat transfer medium

Can also be connected to the hot water heating network

Premium design with round pipes

Operating controls with illuminated LCD screen

With variable temperature adjustment



BHE 50 Plus

Product-No.: 239141




BHE 100 Plus

Product-No.: 238714



BHE 175 T Plus

Product-No.: 238715



Type	BHE 50 Plus	BHE 75 Plus	BHE 100 Plus
Part no.	239141	238713	238714

Technical data

Power supply	1/N ~ 230 V	1/N ~ 230 V	1/N ~ 230 V
Rated voltage	230 V	230 V	230 V
Rated current	2.2 A	3.3 A	4.4 A
Rated output	500 W	750 W	1000 W
Connected load	500 W	750 W	1000 W
Heating output to EN 442 (75/65 – 20 °C)	367 W	571 W	876 W
Heating output F/R – T (70/55 – 24 °C)	125 W	194 W	298 W
Setting range	10–28 °C	10–28 °C	10–28 °C
Number of ribs	20	30	37
IP rating	IP24	IP24	IP24
Protection class	II	II	II
Colour	traffic white, RAL 9016	traffic white, RAL 9016	traffic white, RAL 9016
Height	1090 mm	1590 mm	1830 mm
Width	500 mm	500 mm	550 mm
Depth	117 mm	117 mm	117 mm
Weight	12.00 kg	19.00 kg	23.00 kg



Type	BHE 175 T Plus
Part no.	238715

Technical data

Power supply	1/N ~ 230 V
Rated voltage	230 V
Rated current	7.6 A
Rated output	1750 W
Connected load	1750 W
Heating output to EN 442 (75/65 – 20 °C)	571 W
Heating output F/R – T (70/55 – 24 °C)	194 W
Setting range	10-28 °C
Number of ribs	30
IP rating	IP24
Protection class	II
Colour	traffic white, RAL 9016
Height	1590 mm
Width	500 mm
Depth	130 mm
Weight	20.00 kg

Depth including wall mounting bracket

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.