

# CNS-U 1500 Plus LCD (UK)

CONVECTORS

PRODUCT-NO.: 205870

**High on heat, low on space.**

Sometimes there's just not much room – even for a heater. That is why this wall mounted convector is very slimline. With a minimal depth, it nevertheless delivers outstanding thermal comfort.

**Enjoy a wide range of benefits.** The convector blends into its surroundings perfectly, efficiently delivering cosy warmth. The comfort functions of the integral controller, such as the weekly timer and open window detection, highlight the efficiency and high quality features of the appliance.

**The main features**

Permanent connection with FIL control core

Control unit with self-learning capability: automatic calculation of the preheat time in timer mode

Metal casing and slimline design

Even, quiet, air heating

Operating controls with illuminated LCD screen

ON/OFF switch and overheating protection

Wall mounted convector – ideal as a supplementary heater or interim heater in spring/autumn

Weekly timer, frost protection and open window detection

**CNS-U 500 Plus LCD (UK)**

Product-No.: 205867

**CNS-U 750 Plus LCD (UK)**

Product-No.: 205868

**CNS-U 1000 Plus LCD (UK)**

Product-No.: 205869

**CNS-U 2000 Plus LCD (UK)**

Product-No.: 205871

**CNS-U 2500 Plus LCD (UK)**

Product-No.: 205872

**CNS-U 3000 Plus LCD (UK)**

Product-No.: 205873



|          |                            |                            |                             |
|----------|----------------------------|----------------------------|-----------------------------|
| Type     | CNS-U 500<br>Plus LCD (UK) | CNS-U 750<br>Plus LCD (UK) | CNS-U 1000<br>Plus LCD (UK) |
| Part no. | 205867                     | 205868                     | 205869                      |

## Technical data

|                  |                           |                           |                           |
|------------------|---------------------------|---------------------------|---------------------------|
| Power supply     | 1/N/PE ~240 V             | 1/N/PE ~240 V             | 1/N/PE ~240 V             |
| Rated voltage    | 240 V                     | 240 V                     | 240 V                     |
| Rated current    | 2,1 A                     | 3,1 A                     | 4,2 A                     |
| Connected load   | 0,5 kW                    | 0,75 kW                   | 1,0 kW                    |
| IP rating        | IP24                      | IP24                      | IP24                      |
| Protection class | I                         | I                         | I                         |
| Colour           | signal white,<br>RAL 9003 | signal white,<br>RAL 9003 | signal white,<br>RAL 9003 |
| Setting range    | 5-30 °C                   | 5-30 °C                   | 5-30 °C                   |
| Height           | 450 mm                    | 450 mm                    | 450 mm                    |
| Width            | 348 mm                    | 426 mm                    | 426 mm                    |
| Depth            | 100 mm                    | 100 mm                    | 100 mm                    |
| Weight           | 4.00 kg                   | 4.60 kg                   | 4.60 kg                   |



| Type     | CNS-U 1500 Plus LCD (UK) | CNS-U 2000 Plus LCD (UK) | CNS-U 2500 Plus LCD (UK) |
|----------|--------------------------|--------------------------|--------------------------|
| Part no. | 205870                   | 205871                   | 205872                   |

## Technical data

|                  |                        |                        |                        |
|------------------|------------------------|------------------------|------------------------|
| Power supply     | 1/N/PE ~240 V          | 1/N/PE ~240 V          | 1/N/PE ~240 V          |
| Rated voltage    | 240 V                  | 240 V                  | 240 V                  |
| Rated current    | 6,3 A                  | 8,3 A                  | 10,4 A                 |
| Connected load   | 1,5 kW                 | 2,0 kW                 | 2,5 kW                 |
| IP rating        | IP24                   | IP24                   | IP24                   |
| Protection class | I                      | I                      | I                      |
| Colour           | signal white, RAL 9003 | signal white, RAL 9003 | signal white, RAL 9003 |
| Setting range    | 5-30 °C                | 5-30 °C                | 5-30 °C                |
| Height           | 450 mm                 | 450 mm                 | 450 mm                 |
| Width            | 582 mm                 | 738 mm                 | 894 mm                 |
| Depth            | 100 mm                 | 100 mm                 | 100 mm                 |
| Weight           | 6.00 kg                | 7.70 kg                | 9.20 kg                |



|          |                             |
|----------|-----------------------------|
| Type     | CNS-U 3000<br>Plus LCD (UK) |
| Part no. | 205873                      |

### Technical data

|                  |                           |
|------------------|---------------------------|
| Power supply     | 1/N/PE ~240 V             |
| Rated voltage    | 240 V                     |
| Rated current    | 12,5 A                    |
| Connected load   | 3 kW                      |
| IP rating        | IP24                      |
| Protection class | I                         |
| Colour           | signal white,<br>RAL 9003 |
| Setting range    | 5-30 °C                   |
| Height           | 450 mm                    |
| Width            | 1050 mm                   |
| Depth            | 100 mm                    |
| Weight           | 10.90 kg                  |

Depth including wall mounting bracket

## **Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

[sales@stiebel-eltron.co.uk](mailto:sales@stiebel-eltron.co.uk)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.